



ERCO-TRACK SERIES



ERCO-TRACK SERIES



STRAIGHT TRACKS

The straight track has single-layer and double-layer track designs, and there are different sizes for you to choose from. There are three different power installation methods,

You can bridge and move tracks between tracks according to your needs, providing flexible design for large-span space lighting.

Length of the Pole: 300mm+300mm/500mm+500mm/750mm+750



POWER INSTALLATION METHOD



Embedded Power Supply

CIRCULAR ARC TRACKS


There are various diameter specifications available for the circular arc track: 600mm/ 800mm/ 1000mm/ 1500mm/ 2000mm.

It is suitable for different types of ceilings, creating a spacious and fashionable space, and can create more different shapes according to your needs.the diameter and the circular, square or rectangular shape.

POWER INSTALLATION METHOD









MULTIPLE COLORS AVAILABLE

There are three colors to choose from for the track: black, gold, and nickel. According to the different needs of the space, match them to create your own unique





WORKWEAR SCENARIO

Suitable for workwear scenarios such as restaurants, bars, and front desk.









HOME DECORATION SCENE

Suitable for home decoration scenarios such as living room, study, and dining table at

STRAIGHT TRACK



Model NO. Material Color CT13-Track∑
Aluminum+Copper+Iron
Black/Golden
1000mm/2000mm/2500m



*X=Length Of The Track

CT13-ZJ1 CT13-ED1

 Model NO.
 CT13-ZJ1
 CT13-ED1

 Material
 Copper+PC
 PC

 Color
 Black/Golden
 Black/Golden

 Function
 Connector
 End Cap

ARC TRACK





Model NO.

Material

Color

CT13-Track-RX

Aluminum+Copper+Iron


Black/Golden

600mm/ 800mm/ 1000mm


CT13-Track-XR<u>X</u> Aluminum+Copper+Iron Black/Golden Φ1500mm/Φ2000mm

*X=Diameter Of The Circle

ACCESSORIES



*XXX=Length Of The Pole:300mm+300mm/500mm+500mm 750mm+750mm/1000mm+1000mm



Double-decker tracks

POWER SUPPLY





	External Power Supply	Power Supply On-Track	
	Model NO.	Model NO.	
	CT13-SP100/EX CT13-	CT13-SP100/OT CT13-	
	SP200/EX	SP200/OT	
Model NO.	CT13-SP100/EX	CT13-SP100/OT	
	CT13-SP200/EX	CT13-SP200/OT	
Rated Power	100W 200W	100W 200W	
Body size	L240xW35xH60m	L204xW34xH65mm	
Input voltage	m		
Working voltage	AC180~255V	AC180~255V	
Operating Current	DC48V	DC48V	
Frequency	100W	100W Max.2100mA 200W Max.4200mA	
, ,	Max.2100mA	50/60Hz	
Power factor	200W	≥0.4	
Driver efficiency	Max.4200mA	> 80%	
Dimmable	50/60Hz		
Life Time	≥0.4	No dimming	
	Over current protection-OCP 2.7A	Over current protection-OCP 2.7A	
	Thermal protection-OHP (> 150 °C)	Thermal protection-OHP (> 150 °C)	
	Surge protection-OVP (AC2000V	Surge protection-OVP (AC2000V 10s)	
	10s) Flickers free	Flickers free	
Working Temperature	Form -10°C to 40°C	Form -10°C to 40°C	
Body Material	Aluminum	Aluminum	

PRODUCT INFORMATION



Model NO.

Power CCT

Voltage

CRI

Beam Angle

Material

Color

Life Warranty

Dimendions(mm)

CT13-D30 7W 3000K/4000K/5000K DC48V

> >90 15°/24°/36°/60°

Aluminum Black/Golden

30 000H 3 Years

125 Ф30


CT13-D40 12W 3000K/4000K/5000K DC48V

> >90 15°/24°/36°/60°

Aluminum Black/Golden

30 000H

3 Years



Model NO.

Power

CCT Voltage

CRI

Beam Angle

Material Color

Life

Warranty

Dimendions(mm)



CT13-D50 18W 3000K/4000K/5000K

> DC48V >90 15°/24°/36°/60° Aluminum

Black/Golden 30 000H

3 Years

125

Ф50




CT13-D30A

4W 3000K/4000K/5000K

DC48V >90 105° Arclic

Black/Golden 30 000H

3 Years



Model NO.

Power

CCT

Voltage

CRI Beam Angle

Material

Color Life

Warranty

Dimendions(mm)




CT13-D40A 7W

3000K/4000K/5000K DC48V

105°


30 000H



>90

Arclic Black/Golden

3 Years




CT13-D50A

12W 3000K/4000K/5000K DC48V >90 105°

Arclic

Black/Golden 30 000H

3 Years



Model NO.

Power

CCT

Voltage CRI

> Beam Angle Material

Color Life

Warranty

Dimendions(mm)




7W 3000K/4000K/5000K

CT13-TL7

DC48V >90 15°/24°/36°/60°

Aluminum Black/Golden

> 30 000H 3 Years






CT13-TL12 12W 3000K/4000K/5000K

> DC48V >90

15°/24°/36°/60°

Aluminum Black/Golden

> 30 000H 3 Years



PRODUCT INFORMATION

Model NO. Power Voltage Beam Angle Material

CT13-X60 12W 3000K/4000K/5000K DC48V

>90 15°/24°/36°/60°

Aluminum Black/Golden 30 000H

3 Years

3000K/4000K/5000K

>90 15°/24°/36°/60° Aluminum

DC48V

CT13-X80

18W

Black/Golden 30 000H

3 Years

Dimendions(mm)


CCT


CRI

Color

Life

Warranty





Model NO.

Power CCT

CRI

Voltage

Beam Angle Material

Color Life

Warranty

Dimendions(mm)




CT13-LB5 10W

3000K/4000K/5000K

DC48V >90

30° Aluminum Black/Golden

30 000H 3 Years





65

CT13-LB10

20W

3000K/4000K/5000K

DC48V >90 30°

Aluminum Black/Golden


30 000H

3 Years



Power CCT 3000K/4000K/5000K DC48V Voltage CRI >90 Beam Angle 105° Material Aluminum

Warranty



Black/Golden

30 000H

3 Years

IRTUAL LIGHTS

CT13-DF530

24W 3000K/4000K/5000K

DC48V

>90 105°

Aluminum Black/Golden

30 000H

3 Years





Model NO.

Model NO.

Color

Life

Dimendions(mm)

Power CCT

Voltage CRI

Beam Angle Material

Color Life

Dimendions(mm)

Warranty

CT13-G100

4W


3000K/4000K/5000K

DC48V >90 110°

Aluminum+Glass

Black/Golden 30 000H

3 Years





CT13-R70

4W

3000K/4000K/5000K


DC48V

>90 70°

Aluminum+Arclic

Black/Golden 30 000H

3 Years



PRODUCT INFORMATION



Life	30 000H	
Color	Black/Golden	l H
Material	Aluminum+PC+Arclic	
Beam Angle	110°	
CRI	>90	286
Voltage	DC48V	
ССТ	3000K/4000K/5000K	
Power	15W	뉴
Model NO.	CT13-PL200	T 📵

Dimendions(mm)





+91 96879 16304 | +91 93759 10028 info@virtuallights.in | www.virtuallights.in

DISPLAY GALLERY

M-001, GF, Sg Business Hub, Bhagwat vidyapith, SG Hwy, opp. Agrawal Mall, Gota, Ahmedabad, Gujarat 380060

CORPORATE OFFICE

B-443 to 446, Sumel Business Park, Safal-4, Naroda Rd, Amdupura, Saraspur, Ahmedabad, Gujarat 382345